- the entire range of musical notes...



GamuT

## L7 3-way loudspeaker



## May we present our top of the line Speaker in the L-Series, The L7!

Based on the design experience of the L3 and L5 we have developed breakthrough technology for interior acoustic design and network layout.

These new innovations now bring the L7 even closer to achieving the ultimate goal: bringing the musicians into your living room!

## Listen and be convinced!

Taslaniasl		1 7.
recunicar	specifications	1 /
10011111001	opedineuciono	Now F D

High frequency driver	38mm (1,5") ring radiator, SD-2 neodyme motor, non-resonant aluminium chamber, multiple chamber low compression design, machined aluminium faceplate and stainless steel phase plug	
Mid frequency driver	180mm (7") midrange, powerful vented SD-1 motor, sliced paper cone, low loss linear suspension. Low compression aerodynamic aluminium chassis, spike mounted in cabinet	
Low frequency driver	Two 180mm (7") bass, powerful vented SD-1 motor, sliced paper cone, low loss linear suspension. Low compression aerodynamic aluminium chassis, spike mounted in cabinet	
Crossover network	Interlinked multi order Non-Resonant Linked Impulse (NRLI) technology by GamuT, electromagnetic and circuit optimized Electrically separated board layout	
Cabinet -	High density fibreboard featuring internal skeleton braces. Bitumen damped.	
Appearance:	Bird's eye maple or Roeswood veneer with eleven layers of hand polished high-gloss lacquer	
Frequency response	27 - 60.000Hz	
Sensitivity	90dB @ 2,83V	
Nominal impedance	4 ohms	
Minimum impedance	2.6 ohms @ 220Hz	
Recommended power amplifier	50-300VV	
Input connections	High-quality, gold plated WBT binding posts with 4mm plugs. Bi-wire and Bi-amp capabilit	
Cabinet dimensions (HxWxD)	1280 × 200 × 430 mm (50.4 × 7.9 × 16.9")	
Weight	44kg (99,7lbs)	
Stands	stainless steel spikes	



Oesterled 28 A · DK 4300 Holbaek, Denmark Phone Int. +45 70 20 22 68 · Fax Int. +45 59 43 97 26 E-mail: info@gamutaudio.com · www.gamutaudio.com