

INEX INNOVATION

Photon PreAmp

428 McCormick Street
San Leandro, CA 94577
510-567-8503
510-567-8506 [fax]
www.inexinnovation.com

Dealer and Distributor
Please Contact:
510-326-2985
jimmyko@inexinnovation.com

PRE-A200 and PRE-A202

GENERAL SPECIFICATIONS

Parameter		Specification
Frequency Response		2 Hz to 30 MHz
Maximum Output		2 volts unbalanced 4 volts balanced
Sensitivity	Unbalanced Line Level Inputs	2.5 volts
	Balanced Inputs	5.0 volts
XLR Connector Pin-out (Balanced I/O)		pin 1 ground, pin 2 positive, pin 3 negative
Audio Signal I/O		2 pairs of RCA inputs 2 pairs of RCA outputs 2 pairs of balanced female XLR inputs 1 pair of balanced male XLR outputs
Line Power		100 - 240 VAC
Remote Control Battery		Two AAA
Dimensions	L x W x H	16.5" x 14.2" x 4.3"
		420 x 360 x 110 mm
Weight		16 lb / 7.3 kg

Ordering Information

10,000	PRE-A200	with standard INEX4000 battery pack
12,500	PRE-A202	with dual INEX4000 battery packs for channel separation

The information set forth in this document reflects our best knowledge at the time of issue. The document is subject to changes pursuant to new developments and findings, and a similar reservation applies to the properties of the products described. We undertake no liability for results obtained by usage of our products and information.