

BSM

Series

Series 2 II



Series 7 II



Series 3 II



Series 9 II



Series 4 II



Series 15 II



BSM SERIES SPEAKER SYSTEMS

MODELS	SERIES 2 II	SERIES 3 II	SERIES 4 II	SERIES 7 II	SERIES 9 II	SERIES 15 II
Specifications						
Type	Bass Reflex 2 way 8 inch	Bass Reflex 3 way 8 inch	Bass Reflex 3 way 10 inch	Bass Reflex 3 way 12 inch	Bass Reflex 3 way 12 inch	Bass Reflex 3 way 15 inch
Frequency Response	48 to 18 kHz	48 to 20 kHz	40 to 20 kHz	30 to 20 kHz	30 to 20 kHz	28 to 20 kHz
Recommended Min. & Max. Power	15 to 50 watts	15 to 50 watts	15 to 65 watts	15 to 100 watts	15 to 100 watts	15 to 150 watts
Speaker Impedance	8/4 ohms	8/4 ohms	8/4 ohms	8/4 ohms	8/4 ohms	8/4 ohms
Efficiency 1 watt at 1 meter	91 dB	92 dB	92 dB	94 dB	94 dB	96 dB
Crossover Frequency	4500 Hz	2000 Hz 6000 Hz	2200 Hz 6000 Hz	2000 Hz 5000 Hz	2000 Hz 5000 Hz	1500 Hz 5000 Hz
Transducer size						
Woofer	8"/20cm	8"/20 cm	10"/25cm	12"/30cm	12"/30cm	15"/38cm
Midrange		3"/7.6cm	3"/7.6cm	4 1/2"/11.4cm	4 1/2"/11.4cm	6 1/2"/16cm
Tweeter	3"/7.6cm	2"/5cm	2"/5cm	1"/2.54cm	1"/2.54cm	1"/2.54cm
Finish	Allagash Birch	Allagash Birch	Allagash Birch	Allagash Birch	Allagash Birch	Allagash Birch
Dimensions cm H x W x D inches	58.1x31.4x20.6 22 1/8 x 12 3/8 8 1/8	58.1x31.4x20.6 22 7/8 x 12 3/8 8 1/8	58.1x31.4x20.6 22 7/8 x 12 3/8 8 1/8	66x39.4x28.2 26x15 1/2 x 11 1/8	78.7x36.8x24.8 31x14 1/2 x 9 3/4	76.2x45.5x36.2 30x18x 14 1/4
Weight Kg Lbs	6.6 kg 14 1/2 lbs	6.7 kg 14 3/4 lbs	6.8 kg 15 lbs	12.7 kg 28 lbs	15 kg 33 lbs	21.8 kg 48 lbs
Remarks	Polypropylene Woofer	Polypropylene Woofer	Polypropylene Woofer	Polypropylene Woofer & Midrange Ferro Fluid injected tweeter	Polypropylene Woofer & Midrange Ferro Fluid injected tweeter Mid & High level controls	Ferro Fluid injected tweeter

YOU CAN HEAR THE ENGINEERING

The BSM Series Loudspeakers offer an unusual degree of engineering in speakers that are actually priced below comparable sounding loudspeakers.

All of the BSM speakers have an excellent handling range. They perform equally well from 15 watts to 150 watts of undistorted power; delivering a clean, crisp, faithful reproduction throughout the entire sound spectrum... Furthermore, bass, midrange and treble frequencies remain in balance, regardless of the amplifier power being used.

THE BSM SPEAKERS SOUND BETTER BECAUSE WE PUT MORE INTO IT

- Ferro Fluid injected horn-loaded tweeter. Precision assembled for better dispersion, improved highs and increased power handling.
- Epoxy-bonded copper voice coil, hand wound on aluminium for better heat dissipation utilizing heavier magnets.
- Polypropylene woofers & midranges offering improved uniformity, wider frequency response, accuracy and significantly tighter sound.

- Excellent power handling and efficiency.
- Computer tuned ports maximizing efficiency and deep, rich bass frequencies.
- Streamlined, handsome cabinetry superbly hand crafted.

DEALER

ACE AUDIO-VIDEO LTD.
115-3501 8th ST. E.
SASKATOON, Sask., S7H 0W5

We reserve the right to alter prices and technical specifications as the result of engineering modifications and improvements which may take place without notice. For further information or technical literature, please write to us:

BSM

Series

MITOM INDUSTRIES LIMITED
1140 Eighth Line, Oakville, Ontario,
Canada, L6H 2R4